



WHITE TOPCOAT P.U.
SERIES H360
WHITE

Verinlegno's H360 Series is a two-component white urethane that provides a hard finish that is highly scratch and water resistant with exceptional feel. This product has been formulated to give an unparalleled covering power due to its high opacity. It is very resistant to yellowing and has excellent chemical resistance. The H360 can be tinted to provide a variety of colors, it is formaldehyde free, low in C.O.V and meets all KCMA standards. NOTE: This product can be tinted up to a maximum of 10% (w / w) with the 94POX.

PRODUCT DATA:

PRODUCT CODE: H360
VISCOSITY (20°C): 19 ± 1 sec (FC#4)
SOLID % by WT: 58 ± 2%
SOLID % by WT: 44% (at application)
VOC: 500 g/L
DENSITY: 1.32 ± 0.02
GLOSS: 10°, 20°, 25°, 40°, 60°, 70°
SHELF LIFE: 12 months

APPLICATION:

Surfaces should be well sanded and free of any traces of dust or oil or grease. Before application ensure that both products are thoroughly mixed together.

APPLICATION EQUIPMENT:

SPRAY GUN
PRESSURE TANK
AIR ASSIST

MIXING RATIO:

PRODUCT FORMULATION

H360: 2 parts
B28 CATALYST: 1 part
REDUCER: 400-050 (20-30%)
POT LIFE: 4 hours

TYPICAL SYSTEM:

SUBSTRATE: MDF and any wood essence.
G270 or G140: 1-2 coats 6-7 mils wet
H360: 1 coat 4-5 mils wet

DRYING TIMES:

THICKNESS APPLIED: 4-5 mils wet
DUST FREE: 15 minutes
READY TO HANDLE: 60 minutes
READY TO PACK: 12 hours
RECOAT: 2 hours

STORAGE:

Store in a dry and cool area. Close the container properly after use.

Note: Drying times may vary depending on thickness applied, temperature and/or humidity.

Warning: Its is not recommended to use a product whose pot life has expired.

Recoat: Can be recoated without sanding within 2 hours, after 2 hours it must be sanded (#220-#320).



The customer is responsible for following the recommended application procedures. Failure to adhere to these specifications may result in poor appearance or failure of film. This product is for professional use only. Consult your local representative before applying with other manufacturer products. The customer should test the complete system for adhesion, compatibility and performance prior to full scale application. Please refer to the Safety Data Sheet (SDS) for safety information and precautions prior to using this product. We ONLY guarantee our product to conform to our quality. Our responsibility as manufacturer is limited to the cost of the product. Please feel free to contact us at (819) 367-2201 for any further inquiries regarding this product. All information on this product data sheet is subject to change without notice.