



WB POLYURETHANE SEALER
SERIES W110
CLEAR

DESCRIPTION:

The W110 is a one-component waterbased sanding sealer from the Verinlegno series. It can be utilized for the finishing of flat panels, kitchen doors, moldings and all other components fabricated from wood and MDF. This product was designed to gives excellent clarity and it is very easy to sand.

PRODUCT DATA:

PRODUCT CODE: W110
VISCOSITY (25°C): 75 ± 2 sec (FC#4)
SOLID % by Vol: 30 ± 2%
SOLID % by WT: 28 ± 2% (at application)
VOC: 93 g/L
DENSITÉ: 1.0500
SHELF LIFE: 12 months

MIXING RATIO:

PRODUCT FORMULATION

W110 POLYURETHANE: 1 part
W420 CATALYST: 5% (if desired)
REDUCER Water 10%
POT LIFE: 2 hours maximum at 20°

DRYING TIMES:

THICKNESS APPLIED: 4-5 wet mils
DUST FREE: 30 minutes
READY TO SAND: 3-4 hours

Note: Drying times may vary depending on thickness applied, temperature and/or humidity.

Warning: It is not recommended to use a product whose pot life has expired. A product catalyzed in a metal container can cause discoloration.

APPLICATION:

Surfaces should be well sanded and free of any traces of dust, oil or grease. If using catalyst (W420) 5% ensure that both products are thoroughly mixed, mixing of these 2, products should be done mechanically. The addition of the catalyst in the sealer will improve sanding. Performance and extend the drying time slightly.

TYPICAL SYSTEM:

TEE WIPING STAIN
W110 WB SEALER: 1 or 2 coats 4-5 wet mils
W120 WB TOP COATS: 1 coat 4-5 wet mils
FINISH THICKNESS: 5 mils dry

STORAGE:

To be kept in a dry place at a temperature never under 5°C. After use, cover lids tightly.

The customer is responsible for following the recommended application procedures. Failure to adhere to these specifications may result in poor appearance or failure of film. This product is for professional use only. Consult your local representative before applying with other manufacturer products. The customer should test the complete system for adhesion, compatibility and performance prior to full scale application. Please refer to the Safety Data Sheet (SDS) for safety information and precautions prior to using this product. We ONLY guarantee our product to conform to our quality. Our responsibility as manufacturer is limited to the cost of the product. Please feel free to contact us at (819) 367-2201 for any further inquiries regarding this product. All information on this product data sheet is subject to change without notice.